



NC
N. S. C. ELECTRONICS

PRANESH NANDA
N. S. C. ELECTRONICS

PLOT NO. F-153, INDUSTRIAL AREA, PHASE 8-B, MOHALI (Pb.)
Tel. : 0172-5094641, Mobile : 9815048244 Fax : 0172-5098244
E-mail : praneshnanda@hotmail.com
www.nseelectronics.net, www.nseelectronic.com

Welcome to the world of



N. S. C. ELECTRONICS

Our Name Means a Great deal

Hygienic Products & Security Systems

PRODUCTS RANGE

- ◆ AIR CURTAIN
- ◆ INSECT KILLER
- ◆ AUTO HAND DRYER
- ◆ PVC STRIPS CURTAIN
- ◆ ASSESS CONTROL SYSTEM
- ◆ DRY CLEANING EQUIPMENTS
- ◆ ULTRA SONIC PEST REPELLER

GOOD IDEAS JUST GOT BETTER !!!



INSECT KILLER / FLY KILLER

NSC Insect Killer eliminates mosquitos, flies and other small insect from places of importance. The Flying insects are drawn towards the lure tubes of the unit and die instantaneously on the electrically charged grid. The dead insects get collected in the catchment tray at the bottom for easy disposal *Area covered is only for approximate rough guidance and should not be followed strictly as tested area is effectively measured in total darkness. * No grantee for UV tubes.

MODEL	DIMENSION	TUBES
NSC 01	19" x 16" x 6"	2 x 15 W
NSC 02	12" x 10" x 4"	2 x 8 W
NSC 03	19" x 20" x 6"	2 x 15 W
NSC 04	25" x 16" x 6"	2 x 20 W
NSC 05	25" x 20" x 6"	2 x 20 W
NSC 06	25" x 30" x 6"	2 x 20 W
NSC 07	49" x 16" x 6"	2 x 40 W

PVC STRIP INDUSTRIAL DOOR

THE SOLUTION TO YOUR FOURMOST ENTRY PROBLEMS

NSC Industrial insulating door safe made of clear transparent PVC strips for uninterrupted passage in Factories, Shops floors etc.

They are ideal for :
Automobile Industry Hotels
Engineering Industry Textile Mills
Food/ Meat Processing units Pharmaceuticals units
Cold Storage, Ice-Cream units

SAFE STRIP ADVANTAGES

- It Protects The Enclosed Area From :
Noise, Dust, Fumes, Birds & Insects.
- Save Energy Reduce Heat & Cold Air Loss.
- Maintenance Free Require .
- Only Occasional Wash.
- Improved Working Environment
- A Special Welding Grade-Cold Grade
- Normal in Colour Available



PRODUCT RANGE

NORMAL GRADE :
200 x 2mm : For doors under 2 mtrs. Height.
200 x 3mm : For 2/3 mtrs high doors.
400 x 3mm : For doors over 3 mtrs. high
200 x 5mm : For high air-pressure areas

SUPER COLD STORE GRADE :
200 x 3mm : can with stand upto - 35 C, for Ice-cream freezer & hotel rooms.

WELDING GRADE :
300 x 3mm : to cover welding areas
BUFFER STRIPS :
300 x 2mm : for high abrasion

Size available width 100mm to 1300mm

* Specification are subjective to change without prior notice



NC
N. S. C. ELECTRONICS

AIR CURTAIN is a modern device which, when installed on a door, forms an invisible curtain of continuous air and thus prevents escape of conditioned air as well as entry of outside hot, humid, and polluted air, it, thus, not only cuts down your electricity bill, but also helps in maintaining cleanliness and hygiene to the required standard. NSC Air Curtains are available in various models (both horizontal & vertical) and in four different velocities, They are suited for door opening ranging from 2.5Ft. Wide to 8Ft. Wide and in velocities ranging from 12Mtr. to 30 Mtr./sec and above. These Velocities are divided into four different model for the convenience of our privileged customers.

Technical Specifications

MODEL	DOOR SIZE W H (mm)	RPM	MOTOR CAPACITY	VOLTS
NSC 01	36" 900	2130	1/3 HP	220V
	39" 1000	2130	1/3 HP	220V
	42" 1100	2130	1/3 HP	220V
	48" 1200	2130	1/3 HP	220V
NSC 02	60" 1500	2130	1/3 HPX2	220V
	36" 900	2400	1/2 HP	220V
	39" 1000	2400	1/2 HP	220V
	42" 1100	2400	1/2 HP	220V
NSC 03	48" 1200	2400	1/2 HP	220V
	60" 1500	2400	1/2 HPX2	220V
	36" 900	2700	1.0 HP	440V
	39" 1000	2700	1.0 HP	440V
NSC 04	42" 1100	2700	1.0 HP	440V
	48" 1200	2700	1.0 HP	440V
	60" 1500	2700	1.0 HPX2	440V
	36" 900	3100	1.5 HP	440V
NSC 04	39" 1000	3100	1.5 HP	440V
	42" 1100	3100	1.5 HP	440V
	48" 1200	3100	1.5 HP	440V
	60" 1500	3100	1.0 HPX2	440V

- ★ These air curtain comprise a sleek yet rugged metal body, which is powder coated to give you years of maintenance free use.
- ★ An effective low cost air curtain which can also be used in cold wether to prevent heat loss.
- ★ Motor blower unit are mounted on a re-silint insulated board base to prevent noise.
- ★ Aluminum impellers are statically / dynamically balanced and the housing are made of fully insulated galvanized sheet.
- ★ The heart of the Air curtain is a very heavy duty motor which is smooth and silent in operation. The motor runs of sealed self greasing and continues running that maximize air flow while minimizing power consumption.
- ★ Stainless Steel models are available for any or pharmaceutical industry (with filters).
- ★ Easy installation, quick and prompt.

Velocity Profiles



ENVIRONMENT PROTECTION DATA

- Unwanted air rejection 85-95%
- Small and Noxious odour 85-95%
- Dust and Smoke 85-95%
- Insect rejection 70-80%
- Temperature Loss 15-20%